

DETAILED ACTION

1. In response to Board Decision on 30 June 2010.
2. An examiner's amendment to the record is attached. Please enter entire claim set. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it **MUST** be submitted no later than the payment of the issue fee.

Conclusion

3. Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee.
4. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ellen C Tran whose telephone number is (571) 272-3842. The examiner can normally be reached from 7:30 am to 4:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Joseph G. Ustaris can be reached at (571) 272-7383. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

/ELLEN TRAN/

Primary Examiner, Art Unit 2433

Examiner's Amendment

This listing of the claims will replace all prior versions and listings of the claims in the application:

Listing of Claims:

1. (Currently Amended) A method of preventing a flooding attack on a network server in which a large number of connectionless datagrams are received for queuing to a port on the network server, comprising:

determining, in response to the arrival of a connectionless datagram from a host for a port on the network server, if the number of connectionless datagrams already queued to the port from the host exceeds a prescribed threshold, further comprises calculating the prescribed threshold by multiplying a percentage by the number of available queue slots for the port; discarding the datagram, if the number of connectionless datagram already queued to the port from the host exceeds the prescribed threshold; and

queuing the connectionless datagram to a queue slot of the port, if the number of connectionless datagram already queued to the port from the host does not exceed the prescribed threshold.

2. (Cancelled)

3. (Currently Amended) An apparatus for preventing a flooding attack on a network server in which a large number of datagrams are received for queuing to a port on the server, comprising:

means for determining, in response to a datagram from a host for the port on the network server, if the number of datagrams queued on the port by the host exceeds a prescribed threshold,

further comprises means for calculating the prescribed threshold by multiplying a percentage by a number of available queue slots for the port;

means for discarding the datagram, if the number of datagrams queued on the port by the host exceeds the prescribed threshold; and

means for queuing the datagram to a queue slot of the port, if the number of datagrams queued on the port by the host does not exceed the prescribed threshold.

4. (Cancelled)

5. (Currently Amended) A storage media containing program code that is operable by a computer for preventing a flooding attack on a network server in which a large number of datagrams are received for queuing to a port on the network server, the program code including instructions for causing the computer to execute the steps of:

determining, in response to receiving a datagram from a host for the port on the network server, if the number of datagrams already queued to the port from the host exceeds a prescribed threshold, includes further instructions calculating the prescribed threshold by multiplying a percentage by a number of available queue slots for the port;

discarding the datagram, if the number of datagrams already queued to the port from the host exceeds the prescribed threshold; and

queuing the datagram to a queue slot of the port, if the number of datagrams already queued to the port from the host does not exceed the prescribed threshold.

6. (Canceled)

7. (Canceled)

8. (Canceled)

9. (Previously Presented) The method of claim 1 further comprising:

configuring a maximum number of connectionless datagrams allowed to be queued at the port.

10. (Previously Presented) The method of claim 9 wherein the configuring step further includes configuring a controlling percentage of available queue slots remaining for the port; and wherein the prescribed threshold is based on the controlling percentage of available queue slots remaining for the port.

11. (Previously Presented) The method of claim 1 wherein the port comprises a plurality of queue slots, the method further comprising:

maintaining a number of available queue slots of the plurality of queue slots for the port.

12. (Previously Presented) The apparatus of claim 3 further comprising:

a means for configuring a maximum number of connectionless datagrams allowed to be queued at the port.

13. (Previously Presented) The apparatus of claim 12 wherein the means for configuring further comprises means for configuring a controlling percentage of available queue slots remaining for the port.

14. (Previously Presented) The storage media of claim 5 wherein the computer is the network server.

/ELLEN TRAN/

Primary Examiner, Art Unit 2433